

# SJ 68/32 RT ROUGH TERRAIN SCISSOR SKYJACK™

Dimensions	
<b>A</b> Work Height	11.75 m
<b>B</b> Raised Platform Height	9.75 m
<b>C</b> Lowered Platform Height	1.37 m
<b>D</b> Overall Width	1.76 m
<b>E</b> Overall Length	3.35 m
<b>F</b> Stowed Height (Rails Up)	2.51 m
<b>G</b> Stowed Height (Rails Down)	1.75 m
<b>H</b> Platform Width (Inside Dimension)	1.42 m
<b>I</b> Platform Length (Inside Dimension)	2.44 m
Specifications	
Extension Deck	1.52 m
Ground Clearance	0.20 m
Wheelbase	2.04 m
Weight	3,655 kg
Gradeability	40%
Turning Radius (Inside)	1.52 m
Turning Radius (Outside)	3.96 m
Lift Time (With Rated Load)	39 sec
Drive Speed (Stowed)	6.1 km/h
Drive Speed (Raised)	0.6 km/h
Maximum Drive Height	Full Height
Capacity (Overall)	454 kg
Maximum # of Persons (0 wind rating)	4
Maximum # of Persons	2

## STANDARD FEATURES

- SKYCODED colour coded and numbered wiring system
- Crossover symmetrical 4WD
- Drivable at full height with roll out deck fully extended
- Independent/auto leveling outriggers
- 1.52 m Roll out extension deck
- Diesel engine
- 90° Swing out engine tray
- Multiple wet disc SAHR brakes
- Wiring for AC outlet on platform
- Tilt alarm with drive & lift cut-out
- All motion audible alarm
- Overload sensing system
- Lowering warning system
- Lanyard attachment points
- Operator horn
- Flashing lights
- Hinged railing system
- Forklift pockets and tie down/lift lugs
- Full height spring hinged gate at rear of unit
- Relay based control system
- Foam-filled non-marking tyres

